

# PRO210-N MONITOR SERIES

Introducing the **FORTINGE PRO210-N Monitor** series—designed to enhance your production capabilities with precision and performance.

### Technical Excellence:

Featuring a 21-inch TFT-LCD panel with a 1920x1080 resolution and 16.7 million colors, the PRO210-N ensures stunning clarity in every frame. With brightness 500 cd/m<sup>2</sup> and a contrast ratio of 1000:1, visuals are vibrant, with deep blacks and bright whites.

**Versatile Connectivity:** The PRO210-N supports various inputs, including HDMI, VGA, AV, 3G SDI, and NDI, for seamless integration in studio or on field use, making it a perfect edge product for NDI systems. Equipped with a **robust battery plate system**, it offers flexible power solutions, supporting **V-Mount battery plate**.




**Ergonomic Design:** Lightweight (5kg) with intuitive on-screen controls, it's perfect for both fixed and mobile setups.

**Reliability:** Rigorously tested to meet the highest standards of durability and performance.

 [www.fortinge.com](http://www.fortinge.com)

 [fb.com/fortingevideo](https://fb.com/fortingevideo)

 Zümrütevler Mh. Ertuğrul Sk. No:10  
Akratek Plaza  
Maltepe – Istanbul / Turkey

 +90 (216) 418 11 03

 [info@fortinge.com](mailto:info@fortinge.com)

Head  
Office

 Záhony u. 7. Graphisoft Park D épület 1. emelet 1031 Budapest, Hungary

 [sales@fortinge.com](mailto:sales@fortinge.com)

# FORTINGE

# PRO210-N MONITOR SERIES

## SPECIFICATIONS

General	
Screen Size	21.5"
Color Depth	16.7M
Viewing Angle	89/89 (L/R) 89/89 (U/D)
Aspect Ratio	16:9
Brightness	500 cd/m <sup>2</sup>
Contrast Ratio	1000:1
Backlight	LED
Input Voltage	12V DC
Power Consumption	≤ 36W
Working Temperature	-10°C~50°C
Storage Temperature	-20°C~60°C
Unit Size	360W x 500.4L x 35.6H mm
Unit Weight	5 kg
Box Weight	8 kg
Box Size	50 cm W x 57 cm L x 21 cm H

Input	
1 X BNC	3G SDI
1 X HDMI	HDMI
1 X RJ45	RJ45 (Ethernet)
1 X BNC	Video
Output	
1 X BNC	3G SDI
Audio	
Audio Out	Stereo Headphone, Speaker

SDI Support Format
SD Video: 625i50 PAL , 525i59.94 NTSC
720p(60/59.94/50)
1080p(60/59.94/50/30/29.97/25/24/23.98)
1080PsF(30/29.97/25/24/23.98)
1080i(60/59.94/50)
NDI Support Format
Network Interfaces: 10/100/1000 Ethernet
Decoding up to 2Kp60 streams of Full NDI, NDI/HX
AAC/MP3 Audio Decoders
Support NDI 4.x (Later 5.x and latest Version)
HDMI Support Format
HDMI Interfaces: HDMI 1.4
1280*720p(60/59.94/50/30/29.97/25/24/23.98)
1280*1024p60,1024*768p60,800*600p60
1920*1080p(60/59.94/50/30/29.97/25/24/23.98)
AV Support Format
Color System: PAL,NTSC,SECAM
Video: 1Vp-p @ 75ohm
Audio: 550mV RMS
VGA Support Format
Sync: H:30-75KHZ,V :56-75HZ
Video: 0.7Vp-p @ 75ohm
Resolution: Up to 1920*1080 @ 60HZ



www.fortinge.com

fb.com/fortingevideo

Zümrütevler Mh. Ertuğrul Sk. No:10  
Akratek Plaza  
Maltepe – Istanbul / Turkey

+90 (216) 418 11 03

info@fortinge.com

Záhony u. 7. Graphisoft Park D épület 1. emelet 1031 Budapest, Hungary

sales@fortinge.com

# FORTINGE