

PRO215

Elevate Your
Professional Visual
Experience

The PRO215 Monitor Series is your ultimate solution, combining advanced technology with unmatched reliability. Essential for TV productions, OB van setups, and outdoor broadcasting, the PRO215 offers crystal-clear visuals and seamless performance.

Why Choose PRO215?

- **21.5" Full HD Display:** Enjoy lifelike detail with a 1920 x 1080 resolution.
- **Versatile Inputs & Outputs:** Easily integrate with your system using 3G-SDI, HDMI, DVI-I, and more.
- **Durable Build:** Designed to withstand intensive studio work with an LED backlight and TFT-LCD panel.
- **Precision Control:** Take full command with adjustable settings like Center Marker, Safe Frames, and Zoom.
- **Easy Handling & Setup:** Its compact and lightweight design makes setup and transport a breeze.
- **Power Flexibility:** Equipped with supporting V-Mount battery plates for convenient power options during field operations.



Setting New Standards in Professional Monitoring The PRO215 is crafted with expert feedback to deliver ergonomic design and exceptional functionality. Customizable function keys (F1-F4) and advanced focus adjustment help you achieve perfection in every shot.

Take Your Production to the Next Level Whether in the studio or on location, trust the PRO215 Monitor Series for unparalleled image quality and reliability. Elevate your broadcasts with a monitor that matches the professionalism and flexibility your production demands.



www.fortinge.com

fb.com/fortingevideo

Zümrütevler Mh. Ertuğrul Sk. No:10
Akratek Plaza
Maltepe - İstanbul / Turkey

+90 (216) 418 11 03

info@fortinge.com

Sutton Ct Road. W4 4NN, Chiswick, London - United Kingdom

sales@fortinge.com

Head Office
London Office

FORTINGE

Elevate Your Professional Visual Experience

PRO215

SPECIFICATIONS

General	
Screen Size	21.5"
Color Depth	16.7M
Viewing Angle	89/89 (L/R) 89/89 (U/D)
Aspect Ratio	16:9
Brightness	500 cd/m ²
Contrast Ratio	1000:1
Backlight	LED
Input Voltage	12V DC
Power Consumption	≤ 36W
Working Temperature	-10°C~50°C
Storage Temperature	-20°C~60°C
Unit Size	360W x 500.4L x 35.6H mm
Unit Weight	4.7 kg

Advanced Features
<ul style="list-style-type: none"> • Peaking Focus Assist (Red highlight over parts of the monochrome image in focus) • Center Marker • Screen Marker (80%, 85%, 90%, 93%, 96%, 2.35:1) • Image Freeze • Image Flip (H, V, H/V) • Camera Mode • Pixel-to-Pixel • Check Field (Red, Green, Blue, Mono) • Built-in LED tally indicators

Input	
1 X BNC	3G SDI
1 X HDMI	HDMI
3 X BNC	YPbPr
1 X DV-I	DVI-I
1 X BNC	Video
2 X RCA	Audio (L/R)
Output	
1 X BNC	3G SDI
1 X HDMI	HDMI
3 X BNC	YPbPr
1 X BNC	Video
Audio	
Audio Out	Stereo Headphone, Speaker

SDI Support Format
480i/576i
720p(60/59.94/50/30/29/25/24/23.98)
1080p(60/59.94/50/30/29.97/25/24/23.98)
1080i(60/59.94/50)
HDMI Support Format
480i/576i/480p/576p
720p(60/59.94/50/30/29/25/24/23.98)
1080i(60/59.94/50)
1080p(60/59.94/50/30/29.97/25/24/23.98)
4K UHD 3840x2160p (30/29.97/25/24/23.98Hz)
4096x2160p (24Hz)

www.fortinge.com

fb.com/fortingevideo

Zümrütevler Mh. Ertuğrul Sk. No:10
Akratek Plaza
Maltepe – Istanbul / Turkey

+90 (216) 418 11 03

info@fortinge.com

Sutton Ct Road. W4 4NN, Chiswick, London - United Kingdom

sales@fortinge.com

FORTINGE