

SPECIFICATIONS

CCT (Standard)	2,300K - 10,000K	CCT + (Expanded)	1,800K – 20,000K
CRI	95+	TLCI	95+
SSI (P3200)	87	SSI (D56)	80
TM-30 RG (Average)	100	TM-30 RF (Average)	94
Max Power Output	360W	Max Power Consumption	410W
Color Chipset	OmniColor	Lumens	23,174 lumens
Weather Resistance Rating	IP54	Beam Angle (No Reflector)	70°
Beam Angle (Reflector)	45°	Operating Voltage	AC 100V - 240V / 50 - 60Hz
Max Noise Level	28dBA (30°C / 86°F)	Operating Temperature	-10°C - 40°C / 14°F - 104°F
Storage Temperature	-20°C - 80°C / -4°F - 176°F	Control Methods	On-board, amaran App, DMX via USB-C
Firmware Upgradeable	amaran App, USB-C	Wireless Operating Range	≤80m / ≤262.5ft (Bluetooth)
Screen Type	TFT	Cooling Method	Active Cooling
Max Light Output	17,130 lux @ 1m (No Accessory)		
Max Light Output	17,130 lux @ 1m (No Accessory)		

★ DIMENSIONS

Fixture w/o Mounting Bracket	25.5 x 14.8 x 16.5cm / 10.04 x 5.83 x 6.50in	Fixture w/ Mounting Bracket	25.8 x 19.4 x 25.8cm / 10.16 x 7.64 x 10.16in
AC Power Cable	5m / 16.40ft	Carrying Case	55.0 x 39.0 x 56.0cm / 21.65 x 15.35 x 22.05in

★ WEIGHT

Fixture	3.3kg / 7.28lbs
Carrying Bag	730g / 1.61lbs

📦 WHAT'S IN THE BOX

1x amaran Ray 360c
1x amaran Reflector
1x amaran AC Power Cable (5m)
1x amaran Blue Bowens Mount Protection Cover
1x amaran Ray 360c EPP Carrying Case