

## SPECIFICATIONS

CCT (Standard)	2,300K - 10,000K	CCT + (Expanded)	1,800K – 20,000K
CRI	95+	TLCI	95+
SSI (P3200)	87	SSI (D56)	80
TM-30 RG (Average)	100	TM-30 RF (Average)	94
Max Power Output	660W	Max Power Consumption	750W
Color Chipset	OmniColor	Lumens	45,904 lumens
Weather Resistance Rating	IP54	Beam Angle (No Reflector)	70°
Beam Angle (Reflector)	45°	Operating Voltage	AC 100V - 240V / 50 - 60Hz
Max Noise Level	28dBA (30°C / 86°F)	Operating Temperature	-10°C - 40°C / 14°F - 104°F
Storage Temperature	-20°C - 80°C / -4°F - 176°F	Control Methods	On-board, amaran App, DMX via USB-C
Firmware Upgradeable	amaran App, USB-C	Wireless Operating Range	≤80m / ≤262.5ft (Bluetooth)
Screen Type	TFT	Cooling Method	Active Cooling
Max Light Output	38,500 lux @ 1m (No Accessory)		

## ★ DIMENSIONS

Fixture w/o Yoke	29.9 x 18.6 x 17.9cm / 11.79 x 7.31 x 7.05in	Fixture w/ Yoke	29.9 x 24.1 x 42.0cm / 11.79 x 9.49 x 16.54in
AC Power Cable	5m / 16.40ft	Carrying Case	59.7 x 35.5 x 32.0cm / 23.50 x 13.98 x 12.60in

## ★ WEIGHT

Fixture	5.7kg / 12.57lbs
Carrying Bag	1.11kg / 2.45lbs

## ▶ WHAT'S IN THE BOX

1x amaran Ray 660c
1x amaran Reflector
1x amaran AC Power Cable (5m)
1x amaran Blue Bowens Mount Protection Cover
1x amaran Ray 660c EPP Carrying Case