

<b>System</b>	RHP85 ( Head ) + PH-8B ( Pan handle ) × 2 + P110S ( Pedestal system )		
<b>Payload</b>	25 kg / 55.0 lb	<b>Tilt angle</b>	+90° / -70° ( Limited to ±40° with maximum counterbalance )
<b>Weight</b>	22.2 kg / 48.8 lb	<b>Pan angle</b>	360°
<b>Height</b>	<b>Max</b> : 1745 mm / 68.7"	<b>Counterbalance</b>	<b>Range</b> : 9~20 kg / 20~44 lb ( C.G. 125 mm )
	<b>Min</b> : 995 mm / 39.2"		<b>System</b> : Continuous
<b>Camera plate (Sliding range)</b>	<b>2 Sliding plates ( Standard + Long )</b>	<b>Drag mode</b>	7 STEP
	<b>Standard</b> : ±55 mm / ±2.2" , <b>Long</b> : ±85 mm / ±3.3"	<b>Ball diameter</b>	∅100 mm
<b>Plate attachment (Screw sliding range)</b>	<b>3/8-16UNC × 2</b>	<b>Column section</b>	2 STAGE
	<b>Standard</b> : 102 mm / 4" , <b>Long</b> : 95 mm / 3.7"	<b>Column stroke</b>	750 mm / 29.5" ( Upper : 380 mm / 14.9" , Middle : 370 mm / 14.5" )
<b>Spare screw</b>	<b>3/8-16UNC × 1</b>		Upper column : air pressure , Mid column : manual
	<b>Equipped on the head ( Behind the platform of sliding plate )</b>	<b>Pan handle</b>	PH-8B × 2

**Remarks**

■ Exterior Dimensions (mm)

■ RHP85

