

| | | | |
|--|---|-------------------|--|
| System | TH-M (Monopod) + TH-X H (Head) + TH-M Carrying case | | |
| Payload | 4 kg / 9 lb (*1) | TH-X H | |
| Weight | 2.7kg / 5.9 lb | Tilt+Pan angle | Tilt: +90° / -80° , Pan: 360° |
| Height | ① H : 1890 mm W : 380 mm (※Reference) | Counterbalance | FIX |
| | ② H : 870 mm W : 380 mm (") | Drag mode | FIX |
| Folded length | ③ L : 865 mm (") | Temperature range | -20°C to +60°C / -4°F to +140°F |
| | L : 617 mm (Shortest length for carrying) | Head base | Ball ϕ 65 mm / Flat base with 3/8" female thread |
| Camera plate (Sliding range) | Sliding plate (*2) | TH-M | |
| | ± 30 mm / ± 1.2 " | Tilt+Pan angle | (Locked) FIX / (Unlocked) Tilt: $\pm 20^\circ$, Pan: 360° |
| Plate attachment (Screw sliding range) | 1/4-20UNC screw with video pin | Pipe diameters | Upper: ϕ 34 mm / middle: ϕ 29.5 mm / Lower: ϕ 25 mm |
| | 68 mm / 2.7" | Section | 2 STAGE |
| Monopod camera screw | 1/4-20UNC / 3/8-16UNC | Monopod fixation | Fixing flip lock levers |
| Pan handle | Unique pan handle (Non-telescopic) | Pipe materials | Aluminum |

Remarks

(*1) The monopod's maximum payload does not guarantee a monopod's free-stand position.

(*2) Available for Manfrotto and Sachtler video heads. ※ Not available for all models of Manfrotto and Sachtler.

Do not use the monopod without the free-stand base, this may cause damage to product.

■ Exterior Dimensions (mm)

■ TH-M

(Shortest length for carrying)

■ TH-X H

