

SPECIFICATIONS

CCT	2,700K - 6,500K	CRI	96
TLCI	97	SSI (P3200)	82
SSI (D56)	73	TM-30 RG (Average)	101
TM-30 RF (Average)	93	Max Power Output	26W
Max Power Consumption	30W	Lumens	2,347 lumens
Power Supply Method	USB-C PD	Power Specifications	PD3.0 20V
Operating Voltage	AC 110V - 220V	Operating Temperature	-10°C - 40°C / 14°F - 104°F
Storage Temperature	-20°C - 80°C / -4°F - 176°F	Control Methods	On-board, amaran App, Sidus Link
Firmware Upgradeable	amaran App, Sidus Link	Wireless Operating Range	≤100m / ≤328.08ft (Bluetooth)
Cooling Method	Passive Cooling	Fixture Weight	940g / 2.1lbs
Max Light Output	3,160 lux @ 0.5m		

★ DIMENSIONS

Fixture	29.3 x 22.1 x 2.8cm / 11.5 x 8.7 x 1.1in	Power Adapter	1.8m / 5.9ft
---------	--	---------------	--------------

★ WEIGHT

Fixture	940g / 2.1lbs
---------	---------------

📦 WHAT'S IN THE BOX

1x amaran Verge
1x amaran 30W USB-C PD Power Adapter