Specifications:

Channel Group:	A and B
Antenna:	1/4λ Detachable Antenna
RF Output Power:	30mW
Gain Range:	30dB
Frequency Respon	se: 20Hz to 20kHz
Audio I/O:	Locking 3.5mm TRS Mic & Line Input (Vocal M TX) Locking 3-pin Female XLR Input (Vocal M TLX) Locking 3.5mm TRS Audio Output
Signal Processing:	Low Cut Filter-(40/80/120 Hz) High Frequency Boost-(1 to 4 dB)
Sensitivity:	-41±1dB (0dB=1V/Pa,at 1KHz)
Polar Pattern:	Omnidirectional
Latency:	< 6ms
THD:	<0.5%
Signal-to-Noise Rat	io: >80dB SPL
Recording Format:	WAV
Recording Media:	MicroSD(Up to 32GB)
Power Requirement	s: Built-in Battery or Type-C DC 5V
Built-in Battery Capa	acity: 1500mAh
Battery Life:	12Hours
Battery Charging Tir	ne: 2Hours
Housing:	Metal
Dimensions:	56x80x22mm (Vocal M TX) 45.5x112x44mm (Vocal M TLX) 56x80x22mm (Vocal M RX)
Weight:	125g (Incl.Battery Vocal M TX) 125g (Incl.Battery Vocal M TLX) 135g (Incl.Battery Vocal M RX)
Operating Temperat	ure: 0°C ~ 50°C
Storage Temperatur	e: -20°C ~ 60°C

