

Specifications:

Channel Group:	A and B
Antenna:	1/4λ Detachable Antenna
RF Output Power:	30mW
Gain Range:	30dB
Frequency Response:	20Hz to 20kHz
Audio I/O:	Locking 3.5mm TRS Mic & Line Input (Vocal M TX) Locking 3-pin Female XLR Input (Vocal M TLX) Locking 3.5mm TRS Audio Output
Signal Processing:	Low Cut Filter-(40/80/120 Hz) High Frequency Boost-(1 to 4 dB)
Sensitivity:	-41±1dB (0dB=1V/Pa,at 1KHz)
Polar Pattern:	Omnidirectional
Latency:	< 6ms
THD:	<0.5%
Signal-to-Noise Ratio:	>80dB SPL
Recording Format:	WAV
Recording Media:	MicroSD(Up to 32GB)
Power Requirements:	Built-in Battery or Type-C DC 5V
Built-in Battery Capacity:	1500mAh
Battery Life:	12Hours
Battery Charging Time:	2Hours
Housing:	Metal
Dimensions:	56x80x22mm (Vocal M TX) 45.5x112x44mm (Vocal M TLX) 56x80x22mm (Vocal M RX)
Weight:	125g (Incl.Battery Vocal M TX) 125g (Incl.Battery Vocal M TLX) 135g (Incl.Battery Vocal M RX)
Operating Temperature:	0°C ~ 50°C
Storage Temperature:	-20°C ~ 60°C

What's in the box?

Plug-on XLR transmitter *1
Body-pack transmitter *1
Portable receiver *1
W-LM2 omnidirectional lavalier microphone *1
Locking 3.5mm TRS to 3.5mm TRS audio cable *1
Locking 3.5mm TRS to dual 3-pin XLR audio cable *1
Type-C charging cables *3
Shoe mount adapter *1
Belt clips *2
Antennas *3
Hard suitcase *1
User manual *1
Warranty card *1

