



Quality Products

We Believe in Quality



CORE VALUES

- Innovation
- Quality
- Commitment
- Customer Satisfaction
- Honesty
- Relationship for Life

Electric Blowers



No.	HP	AMP	RPM	Phase	Volts	Shaft Dia.
18	0.10	0.05	2800	1	230	10
25	0.14	0.05	2800	1	230	10
35	0.24	0.9	2800	1	230	12
35	0.25	1	2800	3	440	12
50	0.28	1	2800	1	230	12
50	0.25	1	2800	3	440	12
60	0.58	1.9	2800	1	230	12
60	1	1.5	2800	3	440	12
70	1	2.7	2800	1	230	12
70	1	1.5	2800	3	440	12

All Dimensions Are in MM

Pressure Blowers



Key Features :

- Highly Robust Fabricated Body
- Dynamically Balance Impeller
- Available with Different Desirable Mounting
- Totally Vibration Free
- Also Available in S.S. 304/ S.S. 316

HP	Rotor Size	CFM	Outlet Size	Thickness
0.5	12"	180	3" x 3"	1.6 mm
1.0	15"	250	3" x 3"	1.6mm
2.0	17.5"	400	3" x 3"	1.6mm
3.0	19"	540	3.5" x 3.5"	2mm
5.0	20.5"	660	3.5" x 3.5"	2mm
7.5	22"	975	4" x 4"	2.5mm
10	24"	1350	4" x 4"	2.5mm

All Dimensions Are in Inch

Suction Blowers



Key Features :

- Highly Robust & Durable Fabricated Body
- Dynamically Balance Impeller
- Available with Different Desirable Mounting
- Totally Vibration Free
- Also Available in S.S. 304/ S.S. 316

HP	Rotor Size	Inlet	Outlet
0.5	12" / 2.5"	4"	3.5" x 3.5"
1.0	14" / 2.5"	4"	4" x 4"
2.0	16" / 2.5"	4"	4" x 4"
3.0	18" / 2.5"	5"	6" x 6"
5.0	20" / 2.5"	6"	6" x 6"

All Dimensions Are in Inch

Extra Heavy Duty Four Bearing Grinders



Key Features :

- Highly Robust Study C.I. Body
- High Grade Mild Steel Shaft
- Stator & Rotor are Thin Lamination High Quality Silicon Steel
- Dynamically Balance Rotor Shaft
- High Grade Super Enamelled Copper Wire
- Totally Vibration Free

H.P.	K.W.	R.P.M.	Phase	Volts	Wheel Size (Inch)	Shaft Dia.
2	1.5	2800	3	440	12"x 1.5" & 2"	31.75
3	2.2	2800	3	440	12"x 1.5" & 2"	31.75
5	3.7	2800	3	440	12"x 1.5" & 2"	31.75
7.5	5.5	2800	3	440	12"x 1.5" & 2"	31.75

All Dimensions Are in MM

Bench Grinder



Key Features :

- Highly Robust Study C.I. Body
- High Grade Mild Steel Shaft
- Stator & Rotor are Thin Lamination High Quality Silicon Steel
- Dynamically Balance Rotor Shaft
- High Grade Super Enamelled Copper Wire
- Totally Vibration Free

H.P.	K.W.	R.P.M.	Phase	Volts	Wheel Size	Shaft Dia.
0.5	0.37	2800	1	230	150x20x31.75	15.80
0.5	0.37	2800	1	230	200x20x31.75	15.80
0.75	0.55	2800	1	230	200x25x31.75	19
1	0.75	2800	1	230	250x25x31.75	19
0.5	0.37	2800	3	440	150x20x31.75	15.80
0.5	0.37	2800	3	440	200x20x31.75	15.80
0.75	0.55	2800	3	440	200x25x31.75	19
1	0.75	2800	3	440	250x25x31.75	19

All Dimensions Are in MM

Heavy Duty Bench Polishers



Key Features :

- Highly Robust Study C.I. Body
- High Grade Mild Steel Shaft
- Stator & Rotor are Thin Lamination High Quality Silicon Steel
- Dynamically Balance Rotor Shaft
- High Grade Super Enamelled Copper Wire
- Totally Vibration Free

HP	K.W	Volts	Phase	No. of Bearing	RPM	Spindle Dia.	Spindle len.
2	1.5	440	3	2 & 4	2800	38	250
3	2.2	440	3	2 & 4	2800	38	250
5	3.7	440	3	2 & 4	2800	38	250
7.5	5.5	440	3	2 & 4	2800	38	250

All Dimensions Are in MM

Bench Polishers



Key Features :

- Highly Robust Study C.I. Body
- High Grade Mild Steel Shaft
- Stator & Rotor are Thin Lamination High Quality Silicon Steel
- Dynamically Balance Rotor Shaft
- High Grade Super Enamelled Copper Wire
- Totally Vibration Free

HP	K.W	Volts	Phase	No. of Bearing	RPM	Spindle Dia.	Spindle len.
0.5	0.37	440	3	2	2800	28	200
1	0.75	440	3	2	2800	35	250
2	1.5	440	3	2	2800	38	250
0.5	0.37	230	1	2	2800	28	200
1	0.75	230	1	2	2800	35	250
2	1.5	230	1	2	2800	35	250

All Dimensions Are in MM



Hand Blower

Model	Bearing	Shaft Dia.
18	607	7mm
25	607	7mm
35	607	7mm



DC Blower

Model	Volts
25	12
35	12

Quality Products

Burners

Size	Flanch
200mm	1.5"
280mm	2"
300mm	2"
330mm	2"



Diesel Burners Use :

Farsan & Sweet Furnace,
Paper Packaging Industry,
Industrial Ovens, Powder
Coating Oven, Steam Boiler.

Fuel Types :

Diesel, Gas, Kerosene & Oil



Mfg. By :
JK Manufactures

RAJKOT - GUJARAT(INDIA)

Email : sales@jkmanufactures.com

+91 9409149890

Follow us on



[jkmanufactures](https://www.jkmanufactures.com)