



BHAGWATI[®]
Quality Products

We Believe in Quality



CE
CERTIFIED

ISO
9001:2015

CORE VALUES

- Innovation
- Quality
- Commitment
- Customer Satisfaction
- Honesty
- Relationship for Life

Extra Heavy Duty Four Bearing Grinders



Key Features :

- Highly Robust **Study C.I.** Body
- High Grade Mild Steel **Shaft**
- **Stator & Rotor** are Thin Lamination High Quality **Silicon Steel**
- Dynamically **Balance** Rotor Shaft
- High Grade Super Enamelled **Copper Wire**
- Totally Vibration Free

H.P.	K.W.	R.P.M.	Phase	Volts	Wheel Size (Inch)	Shaft Dia.
2	1.5	2800	3	440	12"x 1.5" & 2"	31.75
3	2.2	2800	3	440	12"x 1.5" & 2"	31.75
5	3.7	2800	3	440	12"x 1.5" & 2"	31.75
7.5	5.5	2800	3	440	12"x 1.5" & 2"	31.75

All Dimensions Are in MM

Bench Grinder



Key Features :

- Highly Robust Study C.I. Body
- High Grade Mild Steel Shaft
- Stator & Rotor are Thin Lamination High Quality Silicon Steel
- Dynamically Balance Rotor Shaft
- High Grade Super Enamelled Copper Wire
- Totally Vibration Free

H.P.	K.W.	R.P.M.	Phase	Volts	Wheel Size	Shaft Dia.
0.5	0.37	2800	1	230	150x20x31.75	15.80
0.5	0.37	2800	1	230	200x20x31.75	15.80
0.75	0.55	2800	1	230	200x25x31.75	19
1	0.75	2800	1	230	250x25x31.75	19
0.5	0.37	2800	3	440	150x20x31.75	15.80
0.5	0.37	2800	3	440	200x20x31.75	15.80
0.75	0.55	2800	3	440	200x25x31.75	19
1	0.75	2800	3	440	250x25x31.75	19

All Dimensions Are in MM

Heavy Duty Bench Polishers



Key Features :

- Highly Robust Study C.I. Body
- High Grade Mild Steel Shaft
- Stator & Rotor are Thin Lamination High Quality Silicon Steel
- Dynamically Balance Rotor Shaft
- High Grade Super Enamelled Copper Wire
- Totally Vibration Free

HP	K.W	Volts	Phase	No. of Bearing	RPM	Spindle Dia.	Spindle len.
2	1.5	440	3	2 & 4	2800	38	250
3	2.2	440	3	2 & 4	2800	38	250
5	3.7	440	3	2 & 4	2800	38	250
7.5	5.5	440	3	2 & 4	2800	38	250

All Dimensions Are in MM

Bench Polishers



Key Features :

- Highly Robust Study C.I. Body
- High Grade Mild Steel Shaft
- Stator & Rotor are Thin Lamination High Quality Silicon Steel
- Dynamically Balance Rotor Shaft
- High Grade Super Enamelled Copper Wire
- Totally Vibration Free

HP	K.W	Volts	Phase	No. of Bearing	RPM	Spindle Dia.	Spindle len.
0.5	0.37	440	3	2	2800	28	200
1	0.75	440	3	2	2800	35	250
2	1.5	440	3	2	2800	38	250
0.5	0.37	230	1	2	2800	28	200
1	0.75	230	1	2	2800	35	250
2	1.5	230	1	2	2800	35	250

All Dimensions Are in MM



Mfg. By :
JK Manufactures

RAJKOT - GUJARAT(INDIA)

Email : sales@jkmanufactures.com

+91 9409149890

Follow us on



[jkmanufactures](https://www.jkmanufactures.com)