INNOJET INNOVATION THAT INSPIRES

SAFETY DATA SHEET

UV-LED IX Black, Cyan, Magenta, Yellow, Light Cyan, Light Magenta, White, & Varnish

1. Identification

IX-BL1416 (Black), IX-CY 1417 (Cyan), IX-MA 1418 (Magenta), IX-YE1419 (Yellow), IX-WH

Product code 1422 (White), IX-LC 1420 (Light Cyan), IX-LM 1421 (Light Magenta), IX-CL1423 (Varnish)

Recommended use UV-LED Curable Printing Ink

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name Innojet Solutions Address 570 Hayden Station

Rd. Unit D

Nu, Offic D

Windsor, CT 06095 1-855-478-3288

E-mail info@innojetsolutions.com

Emergency phone number CHEMTREC 1-800-424-9300

2. Hazard(s) identification

Telephone

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A
Sensitization, skin Category 1A
Reproductive toxicity Category 2

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Specific target organ toxicity, repeated

exposure

Category 1

Category 2

Category 2

Hazardous to the aquatic environment, acute

hazard

Hazardous to the aquatic environment,

long-term hazard

...9

Not classified.

OSHA defined hazards

Environmental hazards

Label elements



Signal word Danger

Hazard statement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May

cause respiratory irritation. Suspected of damaging fertility. Causes damage to organs through

prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear

protective gloves/protective clothing/eye protection/face protection.

UV-LED IX Inks and Varnish SDS US

If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable Response

for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing. If exposed or concerned: Get medical

advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off

contaminated clothing and wash before reuse. Collect spillage.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Storage

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Isobornyl acrylate	5888-33-5	0-15
Tetrahydrofurfuryl acrylate	2399-48-6	10-29
Hexanediol Diacrylate	13048-33-4	10-25
N-vinyl caprolactam	2235-00-9	5-15
Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes	68511-62-6	0-3
Phosphine oxide, diphenyl(2,4,6-trimethylbenzoyl)-	75980-60-8	2-9
Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	162881-26-7	0-2
2-Phenoxyethyl acrylate	48145-04-6	0.2-2
Carbon Black	1333-86-4	0-4
2-Methyl 1-1-(4-Methylthiophenyl)-2-Morpholinpropanone	71868-10-5	0-5
Photoinitiator	Proprietary	0-10

Composition comments Components not listed are either no-hazardous or are below reportable limits.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or

doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin

disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Eye contact

Continue rinsing. Get medical attention if irritation develops and persists

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision

Symptoms/effects May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic reaction.

Dermatitis. Rash. Prolonged exposure may cause chronic effects

Indications of immediate Provide general supportive measures and treat symptomatically. Keep victim under observation.

Medical attention and Symptoms may be delayed

Special treatment needed

General information IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label

where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before

reuse.

UV-LED IX Inks and Varnish SDS US

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2)

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Firefighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Provide adequate ventilation. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components Type Value Nickel. **PEL** 1 mg/m3

5,5'-azobis-2,4,6(1H,3H,5H) -pyrimidinetrione complexes (CAS 68511-62-6)

US. NIOSH: Pocket Guide to Chemical Hazards

Components Type Value

Nickel. **TWA** 0.015mg/m3

5,5'-azobis-2,4,6(1H,3H,5H)

-pyrimidinetrione complexes (CAS 68511-62-6)

Components Value Type Benzophenone (CAS 119-61-9) **TWA** 0.5mg/m3 Components Type Value Hexamethylene diacrylate **TWA** 1 mg/m3 (CAS 13048-33-4) 0.11 ppm

UV-LED IX Inks and Varnish SDS US Issue date: 16-October-2015

923114 Version #: 02 Revision date: 17-June 2025-

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Skin protection Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

9. Physical and chemical properties

Colored liquid. **Appearance**

Physical state Liquid.

Form Colored liquid. Color Colored Mild acrylate. Odor

Odor threshold Not available. Not available. Not available. Melting point/freezing point

Initial boiling point and boiling

range

Not available.

> 199.4 °F (> 93.0 °C) Cleveland Closed Cup Flash point

Evaporation rate Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Not available. **Explosive limit - lower (%)** Explosive limit - upper (%) Not available.

Not available. Vapor pressure

> 1 Vapor density

Vapor density temp. 77 °F (25 °C)

1 - 1.1 Relative density

Relative density temperature 77 °F (25 °C)

Solubility(ies)

Not available. Solubility (water) **Partition coefficient** Not available.

(n-octanol/water)

UV-LED IX Inks and Varnish SDS US Auto-ignition temperatureNot available.Decomposition temperatureNot available.Viscosity3 - 8 mPa·sViscosity temperature77 °F (25 °C)

Other information

Explosive properties Oxidizing properties

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions Hazardous polymerization does not occur.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products

No hazardous decomposition products are known

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause damage to organs through prolonged or repeated exposure by inhalation. May cause

irritation to the respiratory system.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic

skin reaction. Dermatitis. Rash.

Acute toxicity

May cause an allergic skin reaction. May cause respiratory irritation

Components Species Test Results

Phosphine oxide, diphenyl(2,4,6-trimethylbenzoyl)- (CAS 75980-60-8)

Acute Oral

LD50 Rat > 2000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic

UV-LED IX Inks and Varnish SDS US

923114 Version #: 02 Revision date: 17-June 2025- Issue date: 16-October-2015

Components **Species Test Results**

Phosphine oxide, diphenyl(2,4,6-trimethylbenzoyl)- (CAS 75980-60-8)

Acute

Oral

LD50 Rat > 2000 mg/kg

Hexanediol Diacrylate- (CAS 13048-33-4)

Oral

LD50 Rat >5000 mg/kg

Dermal

>3000 mg/kg LD50 Rab

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Causes serious eye irritation.

Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Suspected of damaging fertility. Specific target organ toxicity -May cause respiratory irritation.

single exposure

Specific target organ toxicity -

repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be

harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components **Species Test Results** Phosphine oxide, diphenyl(2,4,6-trimethylbenzoyl)- (CAS 75980-60-8)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) < 100 mg/l, 48 hours Fish LC50 Leuciscus idus < 100 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available. Mobility in soil No data available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component

UV-LED IX Inks and Varnish SDS US Issue date: 16-October-2015

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not

allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in

accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and

the waste disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in

a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after

container is emptied. Empty containers should be taken to an approved waste handling

site for recycling or disposal.

14. Transport information

DOT

UN number UN3082

UN proper shipping name Environmentally hazardous substances, liquid, n.o.s. (Isobornyl acrylate)

Transport hazard class(es)

Class 9
Subsidiary risk Label(s)
Packing group |||

Environmental hazards

Marine pollutant Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions 8, 146, 335, IB3, T4, TP1, TP29

Packaging exceptions 155
Packaging non bulk 203
Packaging bulk 241

IATA

UN number UN3082

UN proper shipping name Environmentally hazardous substance, liquid, n.o.s. (Isobornyl acrylate)

Transport hazard class(es)

Class 9
Subsidiary risk Packing group III
Environmental hazards Yes
ERG Code 9L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA SPECIAL PROVISION: A197-is a new special provision assigned to environmentally substances, UN3077 and UN3082 that allows these substance to be shipped as a "not restricted" provided that the net quantity in any receptacle does not exceed 5 kg or 5L and the packaging used meets defined standards

IMDG

UN number UN3082

UN proper shipping name Transport hazard class(es) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isobornyl acrylate)

Class

Subsidiary risk Packaging group

UV-LED IX Inks and Varnish SDS US

Environmental

Hazards

Marine pollutant Yes F-A, S-F

Special precautions for user Transport in bulk according to Annex Read safety instructions, SDS and emergency procedures before handling.

Not established.

II of MARPOL 73/78 and the IBC Code General information

IMDG Regulated Marine Pollutant. DOT Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All the components of this product are on the TSCA inventory list.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

2-Phenoxyethyl acrylate (CAS 48145-04-6) LISTED Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione LISTED complexes (CAS 68511-62-6)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes	68511-62-6	0-3
2-Phenoxyethyl acrylate	48145-04-6	0.2-2

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

2-Phenoxyethyl acrylate (CAS 48145-04-6)

Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes (CAS 68511-62-6)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Not regulated.

US. New Jersey Worker and Community Right-to-Know Act

2-Phenoxyethyl acrylate (CAS 48145-04-6)

Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes (CAS 68511-62-6)

US. Pennsylvania Worker and Community Right-to-Know Law

2-Phenoxyethyl acrylate (CAS 48145-04-6)

US. Rhode Island RTK

2-Phenoxyethyl acrylate (CAS 48145-04-6)

Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes (CAS 68511-62-6)

UV-LED IX Inks and Varnish SDS US

923114 Version #: 02 Revision date: 17-June 2025- Issue date: 16-October-2015

US. California Proposition 65

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes (CAS 68511-62-6)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date 16-October-2015 **Revision date** 17-June 2025

Version # 02

United States & Puerto Rico

HMIS® ratings Health: 2*

Flammability: 0 Physical hazard: 0

Disclaimer Hilord Chemical Corp cannot anticipate all conditions under which this information and its product,

or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in

the sheet was written based on the best knowledge and experience currently available.

UV-LED IX Inks and Varnish SDS US

Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).