

Product code: 5042

Sector: Industrial

Issue No: 1

Issue Date: 16/12/24

## Millmax 37

Millmax 37 is a premium anti-wear hydraulic oil, specifically engineered to excel in the most demanding modern hydraulic systems, ensuring smooth and efficient equipment operation. Meeting industry standards such as DIN 51524-2, ISO 11158, and the stringent OEM specification Eaton E-FDGN-TB002-E, Millmax 37 provides superior protection and helps prevent downtime.

### Application

Suitable for use in a wide range of applications including industrial hydraulic systems, mobile equipment, injection moulding machines and CNC machinery requiring an ISO VG 37 HLP.

### Features & Benefits

- Exceptional resistance to compression ensures efficient power transfer.
- Zinc-based anti-wear properties protect components, extending equipment lifespan.
- Superior thermal and oxidation stability maintains system cleanliness over time.
- Low-foaming formula minimises aeration and cavitation, ensuring consistent power transfer.
- Demulsification prevents water contamination, reducing the risk of rust, corrosion, and decreased lubricity.
- Compatible with elastomers and seals, enhancing seal life and reducing maintenance requirements.

### Performance Profile

- DIN 51524-2 (HLP)
- ISO 11158 (HM)
- ASTM D6158
- SAE MS 1004
- GB 11118.1-2011
- GM LS-2
- Eaton E-FDGN-TB002-E

### Typical Characteristics

|                      |        |
|----------------------|--------|
| Density @ 15°C, g/ml | 0.856  |
| KV @ 40°C, cSt       | 37.0   |
| KV @ 100°C, cSt      | 6.0    |
| Viscosity Index      | 117    |
| Pour point, °C       | ≥-27°C |
| Flash point, °C      | ≥235°C |