PRODUCT NAME/VISCOSITIES:

MILKING MACHINE OIL

DESCRIPTION:

Manufactured from premium quality, solvent refined base stocks with fourfold additive treatment.

APPLICATION:

Use as received in milking machines, with the added benefit of excellent performance as a high quality general lubricant around the farm.

USER BENEFITS:

- Antiwear and oxidation control.
- Corrosion protection and low foaming tendency.
- Excellent thermal stability promoting a resistance to degradation.
- Good general purpose oil for oil can applications.

PERFORMANCE PROFILE:

- DIN 51524 Part 2.
- Denison HFO and HF2 specifications.
- Vickers HP Vane Pump (mobile and industrial applications).
- Cincinnati Milacron P68 and 70 specifications. P38, 54, 55 & 57 Rust and Oxidation specifications.
- Racine 'S' Pump Test.
- AFNOR Filtration (Wet NFE 48 691).
- Recommended for milking machine vacuum pumps, meeting various o.e.m. specifications.

TYPICAL CHARACTERISTICS:

Specific Gravity @ 15°C 0.880
Kinematic Viscosity @ 100°C 8.9cSt
Kinematic Viscosity @ 40°C 68cSt
Viscosity Index 104

Pour Point °C -8 Flashpoint °C 200

HEALTH AND SAFETY:

Health and Safety Data Sheet 5045 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk



DATA SHEET NO: 5045