

TECHNICAL DATA SHEET



Product code: 5258

Sector: Industrial

Issue No: 3

Issue Date: 28/10/24

MILLTONE A

A premium quality bentone non-melting grease.

Application

Use as received in many bearing applications requiring a non-melt grease. Lubricates up to 200°C.

Can be used for light industrial hammer application ONLY.

Features & Benefits

- Operates at elevated temperatures for long periods.
- High degree of water resistance.
- Does not soften at high temperatures.
- Good rust and oxidation inhibitor.

Typical Characteristics

Appearance	Brown Smooth Grease
NLGI Classification	2
Thickener	Bentone
Solid Lubricant	n/a
Base Oil	Mineral Oil
Base Oil Viscosity @40°C	110cSt
Worked Penetration (IP50)	265 to 295
Drop Point (IP132) °C	>260
Copper Corrosion (IP112)	Pass
Emcor (IP 220) Corrosion Test	00:00
Four Ball Weld Load (IP239)	n/a
Timken OK Load (IP326)	n/a
Operating Temperature Range °C	-20 to +160

*** May be extended to +200°C with more frequent grease applications.**

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk