

TECHNICAL DATA SHEET



Product code: 5317

Sector: Industrial

Issue No: 2

Issue Date: 12/05/22

DELTA 00EP

Lithium based semi-fluid grease with extreme pressure (EP) additives.

Application

Use as received for centralised lubrication systems and gearboxes requiring a semi-fluid grease.

Features & Benefits

- Self-collapsing, will not channel.
- Resistant to water.
- High degree of corrosion protection.

Typical Characteristics

Appearance	Dark Brown Semi-Fluid Grease
NLGI Classification	00
Thickener	Lithium Soap
Solid Lubricant	n/a
Base Oil	Mineral Oil
Base Oil Viscosity @40°C	180cSt
Worked Penetration (IP50)	400 to 430
Drop Point (IP132) °C	n/a
Copper Corrosion (IP112)	Pass
Emcor (IP 220) Corrosion Test	00:00
Four Ball Weld Load (IP239)	315kgs
Timken OK Load (IP326)	23kgs (50lbs)
Operating Temperature Range °C	-30 to +110

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk



MADE IN BRITAIN

Millers Oils Ltd
Brighouse West Yorkshire HD6 3DP UK
Tel: +44(0) 1484 713201
www.millersoils.co.uk