PRODUCT NAME/VISCOSITIES:

DATA SHEET NO: 5351 LM: 28/10/20

MILLFARM XTOU 10w30

DESCRIPTION:

High quality solvent refined base oils with the latest universal additive system designed for the latest tractor designs.

APPLICATION:

Use as received for universal tractor and farm equipment lubrication.

USER BENEFITS:

Super Tractor Oil Universal (STOU) products have been in the market and well accepted for many years. XTOU Tractor Oil Universal has been developed to meet the increased performance demand whilst retaining the traditional benefits of single lubricant lubrication for:-

Engines Transmissions
 Final Drives Power Shifts
 Wet Brakes Power Take-offs

Front Axles

PERFORMANCE PROFILE:

Millfarm XTOU is either approved or meets/exceeds the following performance specifications/tests.

ENGINE	GEAR & TRANSMISSION
API CG-4, SF	API GL4
ACEA E3	Allison C4
• M.B.227.1	Caterpillar TO-2
• MAN M271	• ZF TE- ML 06B, C, F, H, 07B

UTTO	STOU
Massey Ferguson	Massey Ferguson
M1135, M1143, M1145	M1139, M1144, M1145
Ford M2C 134D	• Ford M2C 159B/C
New Holland	New Holland
NH 410B, NH 420A	NH 030C, NH 024C
Case New Holland	• FNH 82009201/2/3
CNH MAT 3525,MAT 3526	
John Deere J20C	John Deere J27A



TYPICAL CHARACTERISTICS:

SAE Viscosity Grade 10w30
Specific Gravity @ 15°C 0.884
Kinematic Viscosity @ 100°C 10.9cSt
Kinematic Viscosity @ 40°C 70cSt
Viscosity Index 122

Pour point °C <-25Flashpoint °C >200Cold Crank Viscosity @ 25°C 7,000cP max

HEALTH AND SAFETY:

Health and Safety Data Sheet 5351 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

