

TECHNICAL DATA SHEET



Product code: 5391 **Sector:** Automotive / Classic
Commercial / Agricultural

Issue No: 4

Issue Date: 01/06/24

UNIVERSAL BRAKE FLUID DOT 4

Brake & Clutch Fluid

Application

Suitable for passenger car, light commercial (LCV) and heavy goods vehicles (HGV). Designed for high performance braking systems where a non-mineral fluid is required and high braking temperatures are experienced.

Performance Profile

U.S. FMVSS No.116 DOT 4, DOT 3
SAE J 1704, SAE J 1703
ISO 4925 (Class 4 & 3)

Typical Characteristics

Equilibrium Reflux Boiling Point	≥260°C
Wet Equilibrium Boiling Point	≥165°C
Kinematic Viscosity @-40°C, cSt	1340
Kinematic Viscosity @100°C, cSt	2.41
Density @ 20°C, g/ml	1.05

Features & Benefits

- Enhanced performance against water absorption, which improves resistance to vapour lock.
- Compatible with DOT 3, 'standard' DOT 4 & DOT 5.1 brake fluid.

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website
www.millersoils.co.uk

Footnotes: Warning: Not to be used in mineral oil systems. Always refer to manufacturer handbook prior to use.