



PRODUCT DATA SHEET



PRODUCT NAME/VISCOSITIES: IT FLUSHING OIL

Product No	5437
Issue No.	2
Issue Date	07/11/12

DESCRIPTION:

A light viscosity penetrative mineral oil containing additives designed to provide enhanced deposit suspension properties.

APPLICATION:

Use as received and prescribed.

USER BENEFITS:

- Specially formulated oil designed to penetrate and suspend typical oil related deposits found in engines.

FLUSHING PROCEDURE:

- The engine and old oil should be brought to their correct operating temperatures before the old oil is drained.
- Refill with IT Flushing Oil and run at normal/low tick-over under no load for 2-3 minutes.
- Absolute maximum running 5 mins.
- Drain the flushing oil and change oil filter.
- Refill with normal engine oil.

TYPICAL CHARACTERISTICS:

Specific Gravity @ 15°C	0.889
Kinematic Viscosity @ 100°C	10.9cSt

HEALTH AND SAFETY:

Health and Safety Data Sheet 5437 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
www.millersoils.co.uk