



SAFETY DATA SHEET

FRAME OIL 2108

Page: 1

Compilation date: 13/05/2008

Revision date: 08/04/2022

Revision No: 1e

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: FRAME OIL 2108

Product code: 5516

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Fuel oil

1.3. Details of the supplier of the safety data sheet

Company name: Millers Oils Ltd
Hillside Oilworks
Rastrick Common
Brighouse
West Yorkshire
HD6 3DP
United Kingdom

Tel: +44 (0)1484 713201

Fax: +44 (0)1484 721263

Email: h.s@millersoils.co.uk

1.4. Emergency telephone number

Emergency tel: NHS Direct +44 111

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Asp. Tox. 1: H304; Carc. 2: H351; Aquatic Chronic 2: H411; -: EUH066

Most important adverse effects: Repeated exposure may cause skin dryness or cracking. May be fatal if swallowed and enters airways. Suspected of causing cancer. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: EUH066: Repeated exposure may cause skin dryness or cracking.

H304: May be fatal if swallowed and enters airways.

H351: Suspected of causing cancer.

H411: Toxic to aquatic life with long lasting effects.

[cont...]

SAFETY DATA SHEET

FRAME OIL 2108

Page: 2

Hazard pictograms: GHS08: Health hazard

GHS09: Environmental



Signal words: Danger

Precautionary statements: P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P501: Dispose of contents/container to an authorised waste disposal company.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

FUELS, DIESEL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
269-822-7	-	-	Carc. 2: H351; Asp. Tox. 1: H304; Aquatic Chronic 2: H411; -: EUH066	70-90%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact. Repeated exposure may cause skin dryness or cracking.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: Inhalation of vapours may cause irritation of nose, throat and airway.

[cont...]

SAFETY DATA SHEET

FRAME OIL 2108

Page: 3

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers. Carbon dioxide. Alcohol resistant foam. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

7.3. Specific end use(s)

Specific end use(s): No data available.

[cont...]

SAFETY DATA SHEET

FRAME OIL 2108

Page: 4

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: If ventilation is insufficient, suitable respiratory protection must be provided.

Hand protection: Impermeable gloves.

Eye protection: Safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Characteristic odour

Evaporation rate: Slow

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Negligible.

Viscosity: Non-viscous

Kinematic viscosity: 3.5 cSt

Viscosity test method: Kinematic viscosity in 10⁻⁶ m²/s at 40°C (ISO 3104/3105)

Boiling point/range°C: 170 - 390

Melting point/range°C: No data available.

Flammability limits %: lower: 1

upper: 6

Flash point°C: >66

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: 220

Vapour pressure: No data available.

Relative density: 0.84

pH: No data available.

VOC g/l: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

[cont...]

SAFETY DATA SHEET

FRAME OIL 2108

Page: 5

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
VAPOURS	RAT	4H LC50	>5	mg/kg
ORAL	RAT	LD50	>5000	mg/kg
DERMAL	RBT	LD50	>2000	mg/kg

Hazardous ingredients:

FUELS, DIESEL

DERMAL	-	LD50	>2000	mg/kg
ORAL	-	LD50	>5000	mg/kg
VAPOURS	-	4H LC50	>5	mg/l

Relevant hazards for product:

Hazard	Route	Basis
Carcinogenicity	--	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact. Repeated exposure may cause skin dryness or cracking.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

[cont...]

SAFETY DATA SHEET

FRAME OIL 2108

Page: 6

Inhalation: Inhalation of vapours may cause irritation of nose, throat and airway.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1202

14.2. UN proper shipping name

Shipping name: GAS Oil

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

[cont...]

SAFETY DATA SHEET

FRAME OIL 2108

Page: 7

14.6. Special precautions for user

Special precautions: No special precautions.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H304: May be fatal if swallowed and enters airways.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

