

TECHNICAL DATA SHEET



Product code: 5535

Sector: Industrial

Issue No: 4

Issue Date: 28/10/24

MILLERVANE 2000

High quality solvent refined base stocks with specially developed additive treatment for vane compressors.

Application

Use as received for 'vane' type compressor lubrication.

Features & Benefits

- Millervane 2000 has been developed to meet the demanding lubricant requirements of specific vane type compressors. The performance of Millervane 2000 has been confirmed in service conditions and found to give excellent results in comparison with market recommended products.
- Millervane 2000 may also be used in reciprocating compressors which require lubricants of this viscosity grade.
- The core performance additive system which was specifically designed and supplied for vane compressor O.E. lubricants has been enhanced by the addition of additional additives which provide additional detergency, anti-oxidation and wear protection. The product also displays good air release and low foaming properties.
- Millervane 2000 has been formulated to protect compressors for 2000+ hours operation.

Performance Profile

- DIN 51506 VD-L, 51506 VC-L, 51506 VB-L
- ISO/DP 6521 DAA, DAB, DAH, DAG

Typical Characteristics

ISO Viscosity Grade	150
Specific Gravity @ 15°C	0.891
Kinematic Viscosity @ 100°C	14.2cSt
Kinematic Viscosity @ 40°C	138.4cSt
Viscosity Index	101
Pour Point °C	-9
Flashpoint °C	220
Colour	Red

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk