

TECHNICAL DATA SHEET



Product code: 5539

Sector: Industrial

Issue No: 3

Issue Date: 28/10/24

CA HAMMER GREASE

A soft adhesive semi-synthetic grease produced for the quarry, civil engineering and demolition industries.

Application

Use as received for use on contact breaker hammers, hydraulic and air operated hammers, chisels and peckers.

Features & Benefits

- Broad operating temperature range in excess of 1,000°C under certain conditions.
- 20% lubricating solids.
- Highly resistant to water.

Typical Characteristics

Appearance	Silver Grey Adhesive Grease
NLGI Classification	2
Thickener	Bentone
Solid Lubricant	Copper, Graphite and Aluminium
Base Oil	Semi-Synthetic
Base Oil Viscosity @40°C	n/a
Worked Penetration (IP50)	n/a
Drop Point (IP132) °C	n/a
Copper Corrosion (IP112)	n/a
Emcor (IP 220) Corrosion Test	n/a
Four Ball Weld Load (IP239)	n/a
Timken OK Load (IP326)	n/a
Operating Temperature Range °C	-20 to + 1,000 under certain conditions

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk