TECHNICAL DATA SHEET



Part code: 5749 Sector: Commercial Vehicle Issue No: 2 Issue Date: 01/06/24

MAXIFLEET ENGINE OIL 20w50

Mineral heavy duty engine oil

Application

A cost-effective heavy duty engine oil suitable for older generation vehicles. Designed to meet the stated manufacturer specifications.

Features & Benefits

- Using modern day technology for added protection in older applications
- Suitable for some automotive applications ideal for use in mixed fleets
- A multiple application product suitable for use in both on and off road applications

Typical Characteristics

Density @ 15°C, g/ml 0.889 Kinematic Viscosity @ 100°C, cSt 18 Flashpoint, °C >200 TBN, mgKOH/g 7

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk

Performance Profile

ACEA E2

API CF-4, CF, SJ

Allison C4

CAT TO-2

Deutz DQC I

MACK EOK/2

MAN 271

Mercedes Benz MB 228.1

MIL-L-2104E, MIL-L-2104D, MIL-L-2104C,

MIL-L-46152D

MTU Type 1

Volvo VDS

Suitable for

API CD, SG, SF

Footnotes: SAPS - Sulphated Ash, Phosphorus & Sulphur, OEM - Original Equipment Manufacturer