

Part code: 5834

Sector: Commercial Vehicle

Issue No: 4

Issue Date: 31/10/24

TRUCKMASTER ENGINE OIL DBX 10w40

Synthetic based, low SAPS.

Application

A premium heavy duty engine oil suitable for the latest engine and exhaust after treatment technology. Designed to meet the stated manufacturer specifications.

Features & Benefits

- Excellent cold flow properties on startup protecting vital components.
- Dynamic Fluid Technology enhances viscosity stability at high temperatures maximizing oil film protection under all conditions.
- Low SAPS technology delivering protection of catalysts, DPF's and EGR's to aid in reducing emissions.
- Extended drain capabilities where applicable, increasing interval periods.
- Bio fuel and gas compatible offering product rationalisation and reducing misapplication.

Typical Characteristics

Density @ 15°C, g/ml	0.866
Kinematic Viscosity @ 100°C, cSt	13.5
Flashpoint, °C	>200
TBN, mgKOH/g	10

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website

www.millersoils.co.uk

Performance Profile

ACEA E6, E7, E8, E9, E11
API CK-4
CAT ECF-3
Cummins CES 20081
Detroit Diesel DDC 93K218
Deutz DQC IV-10 LA
MACK EOS-4.5
MACK EO-OP+
MAN M 3477, M 3271-1
Mercedes Benz MB 228.52, MB 228.51
MTU Type 3.1
Renault RLD-3
Scania LA (Low Ash)
Volvo VDS-4.5

Suitable for

API CJ-4, CI-4 Plus, CI-4
CAT ECF-2, ECF-1a
DAF E6, E7, E9
Deutz DQC III-10 LA, DQC II-10 LA
IVECO 18-1809 TLS E9, 18-1809 NG2
JASO DH-2
MACK EO-N, EO-M+
MAN M 3575
Mercedes Benz MB 228.31, MB 226.9, MB 235.28
MTU Type 2.1
Renault RLD-2, RLD, RXD, RGD
Volvo VDS-3, VDS-2, VDS, CNG
Voith Retarder Class B

Footnotes: SAPS – Sulphated Ash, Phosphorus & Sulphur