



PRODUCT DATA SHEET

**PRODUCT NAME/VISCOSITIES:****P392 HYDRAULIC OIL BLUE**

DATA SHEET NO: 5875

LM: 10/01/11

DESCRIPTION:

A multigrade hydraulic oil of excellent shear stability which promotes outstanding performance over a wide range of temperatures. Meets the specification requirements of Poclain hydraulic fluid.

APPLICATION:

Essentially for Poclain equipment although with its all round capability it may be used with advantage in similar plant, particularly where heavy duty response is required.

USER BENEFITS:

- Additive system provides excellent pump protection by way of anti-rust, anti-foam, anti-wear and anti-oxidation.
- Its high viscosity index and shear stable additive system provides full performance over a wide temperature range.

PERFORMANCE PROFILE:

- DIN 51524 Part 2 and 3

TYPICAL CHARACTERISTICS:

ISO Viscosity Grade	46
Specific Gravity @ 15.4°C	0.876
Kinematic Viscosity @ 100°C	8.8cSt
Kinematic Viscosity @ 40°C	48cSt
Viscosity Index	155
Pour Point °C	-36
Flashpoint °C	180

HEALTH AND SAFETY:

Health and Safety Data Sheet 5875 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
www.millersoils.co.uk