



PRODUCT DATA SHEET



PRODUCT NAME/VISCOSITIES: **FLUSHING ADDITIVE HTS**

Product No	6079
Issue No.	2
Issue Date	21/04/15

DESCRIPTION:

A blend of mineral oil and specific detergent additive package.

APPLICATION:

Use as received to add to bulk oil systems such as heat transfer or any mineral oil based systems working at elevated temperatures.

By addition 5% of the bulk oil capacity. Operate at working temperature for a minimum of 24 hours, more in the case of severe carbon deposits.

USER BENEFITS:

- Specially formulated to work at temperature to penetrate and suspend oil related deposits.
- Ensures the cleanliness of the system prior to re-filling.
- Cost effective in use. No downtime involved whilst the product is circulated.

TYPICAL CHARACTERISTICS:

Specific Gravity @ 15°C	0.836
Kinematic Viscosity @ 100°C	8.64cSt
Pour Point °C	-15
Flashpoint °C	140

HEALTH AND SAFETY:

Health and Safety Data Sheet 6079 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
www.millersoils.co.uk