# **TECHNICAL DATA SHEET**



Product code: 6133 **Sector:** Industrial Issue No: 3 **Issue Date:** 11/04/22

# **RUST PREVENTIVE 2670**

A barium-free oil based product formulated from fully solvent refined mineral oil and selected high performance anti-corrosion additives.

## **Application**

To be used as received and apply by brushing, dipping, swabbing or roller.

#### Features & Benefits

- Free of volatile organic compounds (VOC)
- Barium free
- Easy to apply
- Light viscosity promotes good coverage and excellent draining properties
- Easy removal with everyday solvents such as white spirit

#### Typical Characteristics

| Specific Gravity @ 15°C, g/ml       | 0.854           |
|-------------------------------------|-----------------|
| Kinematic Viscosity @ 40°C, cSt     | 15              |
| Flashpoint, °C                      | 165             |
| Film Thickness, µm                  | 2.3             |
| Coverage, m²/litre                  | 328             |
| Humidity cabinet ASTM-D1748, days   | >30             |
| Salt spray cabinet DIN 50021, hours | 16              |
| Indoor Protection                   | up to 12 months |
| Outdoor Protection                  | up to 6 months  |

## Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk









