

TECHNICAL DATA SHEET



Product code: 6204-1L/5L **Sector:** Commercial Vehicle

Issue No: 1 **Issue Date:** 01/02/24

Diesel Power ECOMAX - For Heavy Duty Use

Heavy Duty Use Diesel fuel treatment for enhanced combustion efficiency and engine cleanliness.

Description

A fuel treatment and detergent package that adds up to 4 cetane numbers (CN). The treatment also provides lubricity for the fuel system, more specifically the fuel pump.

Application

Diesel Power ECOMAX is designed to work with all heavy duty application types of commercial vehicle (HGV), especially Euro 6, Euro 5 and Euro 4 emission compliant vehicles. It is also backward compatible with Euro 3 and older type vehicles, agricultural equipment, plant and off highway.

Dosage Rate

Can be used by adding it to the bulk fuel tank or individual vehicle tanks in the ratio 1 part to 1000 parts fuel [1ml/Litre].

Fuel Dilution Ratios	
Fuel treatment quantity	Fuel quantity
5000ml	5000 L
1000ml	1000 L
500ml	500 L

Directions for use

Add to fuel tank prior to refuelling.

Typical Characteristics

Density @ 15°C, g/ml	0.953
Kinematic Viscosity @ 40°C, cSt	1.55
Flashpoint, °C	60

Features & Benefits

- Increases cetane rating of diesel by up to 4 numbers resulting in an increased power output and MPG.
- Enhanced detergency package for quicker clean up and prolonged diesel injector cleanliness.
- Maintains after-treatment efficiency and helps to invigorate emission control systems.
- Improved combustion and engine cleanliness drastically reduces emissions of hydrocarbons (HC), carbon dioxide (CO₂) and nitrous oxide (NO_x).
- Noticeably improved throttle and engine response at lower revs designed to offer the best of both power and economy.
- Added lubricity in the fuel will reduce wear on components in the fuel system, and increase the longevity of these parts.

Storage Instructions

Store at ambient temperature.
Avoid direct sunlight.
Product efficacy within 24 months of date on bottle if stored according to the manufacturer's instructions.

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website
www.millersoils.co.uk