



PRODUCT DATA SHEET

**PRODUCT NAME/VISCOSITIES:****MILLITRAN 10w40**

DATA SHEET NO: 6220

LM: 12/10/16

DESCRIPTION:

Developed as a UTTO (Universal Tractor Transmission Oil) for tractors and off-highway equipment.

APPLICATION:

Use as received in farm tractor and industrial equipment requiring a 10w40 viscosity combining hydraulic, transmission and final drive with wet brake and power take-off performance.

USER BENEFITS:

The latest technological lubricant developments are employed to provide:-

- Outstanding extreme pressure (E.P.) performance for maximum gear life
- Balanced frictional characteristics for wet brake and power take-off clutches
- Good filterability characteristics for optimum hydraulic operation
- Strong thermal stability for system protection at high loads and temperatures
- High levels of corrosion, rust inhibition and water tolerance

PERFORMANCE PROFILE:

Millitran 10w40 Transmission Fluid meets or exceeds the leading fluid specifications and is recommended for tractor transmissions and wet brake applications.

UTTO/ TRANSMISSION SPECIFICATIONS

- Case New Holland MAT 3525, 3526, 3505
- Massey Ferguson: CMS M1135, M1141, M1143, M1145
- Ford M2C134D, M2C86-B,C
- J.I Case/Case International: MS-1204,1206,1207,1209
- John Deere: JDM J20C, J20D
- Kubota UDT
- Caterpillar TO-2
- Volvo WB101 (VCE 97303) excluding motor grader ZF rear axles
- Allison C4
- ZF TE-ML 06F, 06H
- API GL4
-

HYDRAULIC SPECIFICATIONS

- JCMAS HK P-041 & P042
- Sperry Vickers/ Eaton: M2950S, 1-280-
- Sauer Sunstrand/ Danfoss: Hydrostatic Transmission Fluid



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
www.millersoils.co.uk



PRODUCT DATA SHEET



TYPICAL CHARACTERISTICS:

SAE	10w40
Viscosity @ 40°C	86cSt
Viscosity @ 100°C	13cSt
Density @ 15°C	0.8800
Cold Crank viscosity @ -25°C	7,000cP max

HEALTH AND SAFETY:

Health and Safety Data Sheet 6220 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
www.millersoils.co.uk