

# TECHNICAL DATA SHEET



Product code: 6252

Sector: Industrial

Issue No: 3

Issue Date: 08/08/23

## CYLINDER OIL 460C

A compounded oil of medium viscosity characteristics with added fatty compound.

### Application

Use as received for the lubrication of steam engine cylinders in locomotives and stationary engines working with either superheated or saturated steam.

### Features & Benefits

Cylinder Oil 460C lubricant is designed for medium and high pressure engines and provides:-

- Enhanced lubricating properties.
- High film strength.
- Operation in superheated, dry and wet steam conditions.

### Typical Characteristics

|                             |         |
|-----------------------------|---------|
| Specific Gravity @ 15°C     | 0.901   |
| Kinematic Viscosity @ 100°C | 31.0cSt |
| Kinematic Viscosity @ 40°C  | 462cSt  |
| Flashpoint °C               | 216     |

### Technical & Health and Safety

T: 01484 475060

E: [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)

For H&S info or SDS, please visit our website [www.millersoils.co.uk](http://www.millersoils.co.uk)



**MADE IN BRITAIN**

**Millers Oils Ltd**  
Brighouse West Yorkshire HD6 3DP UK  
Tel: +44(0) 1484 713201  
[www.millersoils.co.uk](http://www.millersoils.co.uk)