



PRODUCT DATA SHEET

**PRODUCT NAME/VISCOSITIES:****HARRIER SAE 20w20**

DATA SHEET NO: 6577
LM: 28/04/15

DESCRIPTION:

Formulated from solvent refined base oils with crankcase detergent, dispersant and anti - wear additives.

APPLICATION:

Use as received where a 20w20, ISO 68 hydraulic oil is required utilizing crankcase performance additives e.g. Liebherr construction and quarrying equipment.

USER BENEFITS:

- Specification required for certain hydraulic applications.
- Extremely cost effective.
- Good detergency to maintain hydraulic system cleanliness.
- Improved circulation from cold start up conditions

PERFORMANCE PROFILE:

API SG/CF/CF2

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	20
Specific Gravity @ 15°C	0.873
Kinematic Viscosity @ 100°C	8.8cSt
Kinematic Viscosity @ 40°C	59.8cSt
Viscosity Index	121
Pour Point °C	-18
Flashpoint °C	210

HEALTH AND SAFETY:

Health and Safety Data Sheet 6577 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
www.millersoils.co.uk