

TECHNICAL DATA SHEET



Product code: 7660

Sector: Industrial

Issue No: 2

Issue Date: 10/08/23

KNITTING OIL ISO 22

Premium quality, pale coloured base oils with performance enhancing additives.

Application

Used as an emulsifiable needle and knitting machine lubricant.

Product should be stored under cover. Avoid extremes of temperature and protect from frost.

Features & Benefits

- Pale coloured in use. Easily emulsified and scoured

Performance Profile

- Inhibited against multi metal corrosion
- Enhanced ash free E.P. performance
- Synthetic lubricity additive
- Product readily strikes in water
- Excellent lubrication under extreme conditions
- Highly resistant to heat degradation
- Low friction losses

Typical Characteristics

Property	ISO 22
Specific Gravity	0.885
Kinematic Viscosity @ 40°C	22cSt
Colour	Pale yellow
pH @ 5.0% emulsion	Neutral
Flash point (PMCC)	>160oC
Emulsification Test	Pass
4 ball wear scar (1 hour @ 40kg)	0.45 mm diam
Pour point	-25oC
Copper Corrosion test	1a

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk



MADE IN BRITAIN

Millers Oils Ltd
Brighouse West Yorkshire HD6 3DP UK
Tel: +44(0) 1484 713201
www.millersoils.co.uk