PRODUCT NAME/VISCOSITIES:

MILLFARM XTOU 15w40

DATA SHEET NO: 7859

16/09/14

DESCRIPTION:

High quality solvent refined base oils with universal additive system designed for the latest tractor requirements.

APPLICATION:

Use as received for universal tractor and farm equipment lubrication where a 15w40 viscosity is required.

USER BENEFITS:

Super Tractor Oil Universal (STOU) products have been in the market and well accepted for many years. XTOU Tractor Oil Universal has been developed to meet the increased performance demand whilst retaining the traditional benefits of single lubricant lubrication for:-

Engines Transmissions
 Final Drives Power Shifts
 Wet Brakes Power Take-offs

Front Axles

PERFORMANCE PROFILE:

Millfarm XTOU is either approved or meets/exceeds the following performance specifications/tests.

ENGINE	GEAR & TRANSMISSION	
API CG-4, SF	API GL4	
ACEA E3	Allison C4	
• M.B.227.1	Caterpillar TO-2	

UT	STOU		OU
•	Massey Ferguson	•	Massey Ferguson
	M1135, M1143, M1145		M1139, M1144, M1145
•	Ford M2C 134D	•	Ford M2C 159B/C
•	JI Case/Case Int: MS-1204, 6, 7,	•	Ford New Holland 82009201/2/3
	9		
•	CNH MAT 3525,MAT 3526	•	John Deere J27A
•	John Deere J20D	•	ZF TE- ML 06B, 06C, 07B



TYPICAL CHARACTERISTICS:

SAE Viscosity Grade 15w40
Specific Gravity @ 15°C 0.880
Kinematic Viscosity @ 100°C 12.77cSt
Kinematic Viscosity @ 40°C 90.8cSt
Viscosity Index 138

Pour point °C -36 Flashpoint °C 220 Cold Crank Viscosity @ 25°C 7,000cP max

HEALTH AND SAFETY:

Health and Safety Data Sheet 7859 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

