

TECHNICAL DATA SHEET



Product code: 7875

Sector: Industrial

Issue No: 5

Issue Date: 20/08/25

MILLERGREASE SYNTH HT 2

A premium quality lithium complex grease reinforced with Extreme Pressure (EP) anti-corrosion additives and PTFE.

Application

Designed for use in anti-friction and plain bearings subjected to high temperatures over extended periods without leaving dry residues associated with conventional greases.

Features & Benefits

- Excellent high temperature capability, reducing carbon residues and extending the lubrication intervals.
- Also provides excellent lubrication at sub-zero temperatures.
- Extreme pressure additives and PTFE extend component life.
- Excellent corrosion protection of components and working surfaces.
- Highly resistant to water washout.

Typical Characteristics

Appearance	Brown Smooth Grease
NLGI Classification	2
Thickener	Lithium Complex
Base Oil	Synthetic
Worked Penetration (ASTM D217)	265-295
Drop Point (ASTM D2265) °C	>260
Copper Corrosion (ASTM D4048)	Pass
Emcor (ASTM D6138) Corrosion Test	2,2
Water Washout @ 79°C % (ASTM D1264)	5.8
Four Ball Weld Load (IP239)	355kgs
Operating Temperature Range °C	-40 to +180