

TECHNICAL DATA SHEET



Product code: 7985 **Sector:** Motorcycle, Scooter & ATV

Issue No: 5

Issue Date: 01/11/24

ZFS 2T

Fully synthetic 2 stroke engine oil for use in motorcycle, scooter & ATV applications.

Description

A fully synthetic 2 stroke oil. Formulated using synthetic base oils and ashless additives to give long-term protection and high performance.

Application

Suitable for use in motorcycle, scooter and ATV applications including karts engines where a 2 stroke oil is required.

Directions for use

If automatic lubrication system add to the designated tank. If self-mix then mix with petrol at the ratio recommended by the equipment manufacturer typically 40:1 up to 50:1.

Performance Profile

API TC, TB, TA
JASO FD, FC, FB
ISO-L-EGD, ISO-L-EGC

Features & Benefits

- Fully synthetic base oils providing a low smoke formulation
- Ashless additive package prevents ring sticking, piston seizure and plug fouling.
- Improves sealing between piston, piston rings and cylinder to increase engine efficiency.
- Dyed 'blue' for easy recognition of the product and treated fuel.

Typical Characteristics

Density @ 15°C, g/ml	0.855
Kinematic Viscosity @ 100°C, cSt	7.9
Flash Point, °C	75
Colour	Blue

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website
www.millersoils.co.uk