

TECHNICAL DATA SHEET



Product code: 8045 **Sector:** Automotive (Passenger Car & LCV) **Issue No:** 4 **Issue Date:** 27/01/25

XF PREMIUM ENGINE OIL C2 ECO 0w30

Fully synthetic, mid SAPS, for use in petrol/gasoline, diesel and hybrid applications

Application

A premium engine oil with OEM Acknowledgement formulated using the latest technology for OEM applications requiring a C2 0w30 viscosity, predominantly for Ford and Jaguar Land Rover.

Performance Profile

ACEA C2

Ford WSS-M2C950-A

**Jaguar Land Rover STJLR.03.5007
(OEM Acknowledgement)**

Suitable for

API SN

Asian manufacturers (where an ACEA C2 oil is recommended)

Typical Characteristics

Density @ 15°C, g/ml	0.845
Kinematic Viscosity @ 100°C, cSt.	9.7
Flashpoint, °C	>200

Features & Benefits

- XF Premium engine oil with Millers Oils Dynamic Fluid Technology (DFT) provides enhanced low temperature flow when cold starting, instantly protecting the vital components of the engine from the very start of every journey.
- XF Premium engine oil with DFT maximises viscosity stability at high temperatures. This reduces engine wear giving superior protection for components including pistons, rings, timing chain, bearings and valve lifters.
- DFT specifically engineered to enhance engine cleanliness, delivering improved fuel economy, reduced emissions and extended service drain capability.
- DFT complements and utilises latest mid SAPS technology protecting after treatment systems such as particulate filters, Selective Catalytic Reduction (SCR) and AdBlue delivering our ultimate soot control and environmental protection.
- DFT delivers outstanding instant protection under hot and cold temperatures, whilst simultaneously reducing fuel consumption and lowering exhaust emissions.
- XF Premium engine oil with DFT is specifically formulated for use in all hybrid systems including self-charging hybrid electric vehicles (HEV) and plug in hybrid electric vehicles (PHEV).

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website
www.millersoils.co.uk

Footnotes: SAPS – Sulphated Ash, Phosphorus & Sulphur, DFT – Dynamic Fluid Technology, OEM – Original Equipment Manufacturer