

TECHNICAL DATA SHEET



Product code: 8049 **Sector:** Automotive (Passenger Car & LCV) **Issue No:** 5 **Issue Date:** 03/02/25

XF PREMIUM ENGINE OIL C5 V 0w20

Fully synthetic, mid SAPS, for use in petrol/gasoline, diesel and hybrid applications.

Application

A premium OEM approved engine oil (formerly known as XF Premium C5 VW 0w20) formulated using the latest technology for applications requiring a C5 0w20 viscosity designed for Volkswagen Audi Group (VAG) including Bentley, Cupra, Seat, Skoda and Porsche.

Performance Profile

ACEA C5

Porsche C20

VW 508 00 / 509 00 (OEM Approved)

Suitable for

Ford WSS-M2C956-A1

Audi, Cupra, Bentley, Seat, Skoda, Porsche, Volkswagen.

Typical Characteristics

Density @ 15°C, g/ml	0.844
Kinematic Viscosity @ 100°C, cSt.	8.4
Colour	Pale green
Flashpoint, °C	>200

Features & Benefits

- XF Premium engine oil with Millers Oils Dynamic Fluid Technology (DFT) provides enhanced low temperature flow when cold starting, instantly protecting the vital components of the engine from the very start of every journey.
- XF Premium engine oil with DFT maximises viscosity stability at high temperatures. This reduces engine wear giving superior protection for components including pistons, rings, timing chain, bearings and valve lifters.
- DFT specifically engineered to enhance engine cleanliness, delivering improved fuel economy, reduced emissions and extended service drain capability.
- DFT complements and utilises latest mid SAPS technology protecting after treatment systems such as particulate filters, Selective Catalytic Reduction (SCR) and AdBlue delivering our ultimate soot control and environmental protection.
- DFT delivers outstanding instant protection under hot and cold temperatures, whilst simultaneously reducing fuel consumption and lowering exhaust emissions.
- XF Premium engine oil with DFT is specifically formulated for use in all hybrid systems including self-charging hybrid electric vehicles (HEV) and plug in hybrid electric vehicles (PHEV).

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website

www.millersoils.co.uk

Footnotes: SAPS – Sulphated Ash, Phosphorus & Sulphur, DFT – Dynamic Fluid Technology, OEM – Original Equipment Manufacturer