

TECHNICAL DATA SHEET



Product Code: 8058 **Sector:** Automotive (Passenger Car & LCV) **Issue No:** 3 **Issue Date:** 01/02/24

TRIDENT PROFESSIONAL ENGINE OIL ECO 5w30

Fully synthetic, full SAPS, for use in petrol, diesel and hybrid engines.

Application

A professional engine oil suitable for the latest engine technology. Designed to meet OEM specifications. Recommended for engines requiring a 5w30 viscosity targeting Ford, Jaguar Land Rover and Asian manufacturers.

Performance Profile

ACEA A5/B5
API SL, CF

Suitable for

ACEA A1/B1
Chrysler MS-6395
Dacia
Ford WSS-M2C913-D, Ford WSS-M2C913-C
Ford WSS-M2C913-B
ILSAC GF-4
Jaguar Land Rover STJLR.03.5003
Renault RN0700
Asian manufacturers

Features & Benefits

- Excellent low temperature flow when cold starting, helping to instantly protect vital components.
- Viscosity stability at high temperatures, delivering reduced wear and tear on the engine and its components.
- Formulated with technology to provide engine cleanliness and durability which improves fuel economy, reduces emissions and provides extended drain capability.
- Millers Oils stop start technology delivers instant protection under hot or cold conditions.

Typical Characteristics

Density @ 15°C, g/ml	0.847
Kinematic Viscosity @ 100°C, cSt.	10.2
Flashpoint, °C	>200

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website
www.millersoils.co.uk

Footnotes: SAPS – Sulphated Ash, Phosphorus & Sulphur, OEM – Original Equipment Manufacturer