

Part code: 8189

Sector: Commercial Vehicle

Issue No: 2

Issue Date: 01/06/24

MULTIFLEET ENGINE OIL 5w30

Fully synthetic, low SAPS

Application

A heavy duty engine oil suitable for all modern engine technology, up to and including EURO 6. Designed to meet the stated manufacturer specifications.

Features & Benefits

- Lower viscosity grade improves fuel economy vs. higher viscosity oils.
- Excellent cold flow properties on startup protecting vital components.
- Low SAPS technology delivering protection of catalysts, DPF's and EGR's to aid in reducing emissions.
- Extended drain capabilities where applicable, increasing interval periods.

Typical Characteristics

Density @ 15°C, g/ml	0.855
Kinematic Viscosity @ 100°C, cSt	12
Flashpoint, °C	>200
TBN, mgKOH/g	10

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk

Performance Profile

ACEA E6, E9
API CK-4
CAT ECF-3
Cummins CES 20086
Detroit Diesel DDC 93K222
Deutz DQC IV-18 LA, DQC III-18 LA
MACK EO-S 4.5
MAN M 3477, M 3271-1
Mercedes Benz MB 228.51
MTU Type 2.1
Renault RLD-4, RLD-3
Volvo VDS-4.5

Suitable for

API CJ-4, CI-4 Plus, CI-4, SL
CAT ECF-2, ECF-1a
Cummins CES 20081
DAF E9
Detroit Diesel DDC 93K218
Deutz DQC IV-10 LA, DQC III-10 LA, DQC II-10 LA
IVECO 18-1804 TLS E6
MACK EO-OP+, EO-N, EO-M+
MAN M 3575
Mercedes Benz MB 228.31, MB 226.9
Renault RLD-2, RLD, RGD, RXD
Volvo VDS-5*, VDS-4, VDS-3, VDS-2, VDS, CNG

*This product can be used where Volvo VDS-5 specification is required with the exception of potential fuel economy benefits.

Footnotes: SAPS – Sulphated Ash, Phosphorus & Sulphur, OEM – Original Equipment Manufacturer