

Part code: 8193

Sector: Commercial Vehicle

Issue No: 2

Issue Date: 01/06/24

MAXIFLEET ENGINE OIL 15w40

Mineral heavy duty engine oil

Application

A cost-effective heavy duty engine oil suitable for older generation vehicles. Designed to meet the stated manufacturer specifications.

Features & Benefits

- Using modern day technology for added protection in older applications
- Suitable for some automotive applications ideal for use in mixed fleets
- A multiple application product suitable for use in both on and off road applications

Typical Characteristics

Density @ 15°C, g/ml	0.876
Kinematic Viscosity @ 100°C, cSt	14
Flashpoint, °C	>200
TBN, mgKOH/g	7

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website

www.millersoils.co.uk

Performance Profile

ACEA E2
API CF-4, CF, SJ
Allison C4
CAT TO-2
Deutz DQC I
MACK EOK/2
MAN 271
Mercedes Benz MB 228.1
MIL-L-2104E, MIL-L-2104D, MIL-L-2104C,
MIL-L-46152D
MTU Type 1
Volvo VDS
ZF TE-ML-06F, ZF-TE-ML-07B

Suitable for

API CD, SG, SF

Footnotes: SAPS – Sulphated Ash, Phosphorus & Sulphur, OEM – Original Equipment Manufacturer