

Part code: 8336

Sector: Commercial Vehicle

Issue No: 2

Issue Date: 01/06/24

TRUCKMASTER GEAR OIL 75w90

Fully synthetic gear oil for applications where an extra high performance lubricant is required

Application

Fully synthetic gear oil for applications where an extra high performance lubricant is required.

Suitable for

API GL-4, GL-5
SAE J2360 (MIL-PRF-2105 E)
MIL-L-2105 D/C/B
MT-1
Arvin Meritor 0-76-N
Detroit Diesel DFS 93K219.01
MAN M341 Z2, MAN M342 M3, MAN M342 S1
MAN M 3343 S
Mack GO J
MB 235.11, MB 235.8, MB 235.1
Renault B0032/2-3
Scania STO 2:0 A FS, Scania STO 2:0 A,
Scania STO 1:0
Volvo 97315, Volvo 97312
ZF TE-ML 02B, 05A, 05C, 07A, 12B, 12L, 12N,
16A, 16B, 16C, 17B, 19B, 19C, 21A, 24A
DAF, Eaton, Iveco, Renault

Features & Benefits

- Synthetic formulation gives longer oil life and improved cleanliness
- Low temperature operations, free flowing down to -40°C
- Ensures easier gear shifting
- Potential for improved fuel economy
- Ability to reduce temperatures in 'hot' running axles

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website
www.millersoils.co.uk

Typical Characteristics

Density @ 15°C, g/ml	0.874
Kinematic Viscosity @ 100°C, cSt	14.2
Flashpoint, °C	>200