

Part code: 8338

Sector: Commercial Vehicle

Issue No: 4

Issue Date: 01/06/24

TRUCKMASTER ATF MT

Premium automatic transmission fluid technology

Application

Premium automatic transmission fluid technology blended into selected synthetic base fluids.

Suitable for

Allison TES 389, Allison C4 (TES 228), Allison C3
Allison V370

Cat T0-2

Clark Powershift Systems

Denison Systems

Ford WSS M2C166H, M2C138CJ, Ford Mercon

GM Dexron IIIH, GM Dexron IIIG, GM Dexron IIE,

GM Dexron IID, GM Dexron II

GM Type A Suffix A (TASA)

Hagglunds Systems

MAN M339 Type Z2, MAN M339 Type Z1, MAN
M339 Type V2, Type V1, Type L2, Type L1, Type F

MB 236.10, MB 236.9, MB 236.7, MB 236.6 MB

236.5, MB 236.3, MB 236.2

Racine Systems

Rexnord Systems

Sperry-Vickers Systems

Sundstrand Systems

Voith H55.6336, Voith H55.6335.XX

Volvo 97341, Volvo 97340

ZF TE-ML 02F, 03D, 04D, 05L, 09X, 11A, 11B, 14A,
14B, 14C, 17C, 20B

Suitable for Power Steering Applications

Features & Benefits

- Easier shifting, even at lower temperatures
- Lower maintenance costs
- Longer drain periods
- Outstanding low temperature fluidity which provides exceptional cold flow properties

Typical Characteristics

Density @ 15°C, g/ml	0.858
Kinematic Viscosity @ 100°C, cSt	7.3
Flashpoint, °C	>200
Colour	Red

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website
www.millersoils.co.uk