

TECHNICAL DATA SHEET



Product code: 8375 **Sector:** Automotive (Passenger car & LCV)

Issue No: 5 **Issue Date:** 01/06/24

XF Premium MTF 75w80

Fully synthetic gear oil for use in gearboxes.

Application

A premium OEM gear oil formulated using the latest technology for gearbox applications requiring a 75w80 viscosity. Predominantly for European and Asian manufacturers.

Suitable for

API GL-4, GL-5

BMW Group Inc. Mini, Rolls Royce
MTF LT-2, P/N 83 22 0 309 031
Fiat Chrysler Automobiles Inc. Abarth,
Alfa Romeo, Chrysler, Dodge, Ferrari, Fiat,
Jeep, Lancia, Maserati (pre-2021),
9.55550-MZ12, 9.55550-MZ10
Ford M2C200-C3
General Motors Inc. Buick, Cadillac, Chevrolet,
GMC, Opel, Saturn, Vauxhall (pre-2017),
GM 1940768
Honda MTF-III, MTF-II, MTF
Land Rover/Rover/Mini MTF 94
Nissan MT-XZ
Subaru P/N SOA748V0100
PSA Inc. Peugeot, Citroen, DS,
B71 2330, P/N 9730.A2
Volvo 1161681, 97309, 97308

EZL-848
Tranself NFJ, NFP, TRJ, TRP, TRT, TRX, TRZ

Features & Benefits

- XF Premium gear oil provides enhanced low temperature flow when cold starting, instantly protecting the vital components of the gearbox from the very start of every journey.
- XF Premium gearbox oil maximises viscosity stability at high temperatures. This reduces gearbox wear giving superior component protection including gear teeth, shafts and bearings.
- Delivers outstanding lubrication and instant protection under hot and cold temperatures.
- XF Premium gear oil is specifically formulated for use in hybrid systems including self-charging hybrid electric vehicles (HEV) and plug in hybrid electric vehicles (PHEV).

Typical Characteristics

Density @ 15°C, g/ml	0.858
Kinematic Viscosity @ 100°C, cSt	8.0
Flash Point, °C	>220

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website
www.millersoils.co.uk

Footnotes: P/N – OEM Part Number