

TECHNICAL DATA SHEET



Product code: 8382 **Sector:** Automotive (Passenger & LCV) **Issue No:** 5 **Issue Date:** 01/06/24

Trident Professional ATF UN

Automatic transmission fluid for use in automatic gearboxes & power steering systems.

Application

A professional automatic transmission fluid developed for multi vehicle applications. This ATF can also be used in certain power steering systems.

Suitable for

Ford Mercon (XT-2-QDX), WSS-M2C185A, WWS-M2C166H, WWS-M2C138CJ
General Motors Inc. Buick, Cadillac, Chevrolet, GMC, Opel, Saturn, Vauxhall (pre-2017), GM Dexron IIE, Dexron IID, Dexron II, Dexron B, Type A Suffix A (TASA), Type A
Mazda ATF D-II
Mercedes-Benz MB 236.7, 236.6, 236.3, 236.2, 236.1, 235.71
Toyota ATF D-II

Features & Benefits

- Excellent low temperature flow when cold starting, instantly protecting the vital components of the gearbox from the very start of every journey.
- High resistance to oxidation and degradation.
- Ensures a smooth transmission of power.

Typical Characteristics

Density @ 15°C, g/ml	0.855
Kinematic Viscosity @ 100°C, cSt	7.5
Flash Point, °C	210
Colour	Red

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website
www.millersoils.co.uk

Footnotes: The colour of the oil is not an indicator of performance, the characteristics of the oil are linked to the claim set of the product. If the oil meets the required specification but does not match the colour of the genuine Original Equipment Manufacturer (OEM) oil, it is still suitable to be used and including when the vehicle is under warranty.