

TECHNICAL DATA SHEET



Product code: 8597 **Sector:** Automotive (Passenger Car & LCV) **Issue No:** 1 **Issue Date:** 01/09/24

EE PERFORMANCE ENGINE OIL C3 0w30

Fully synthetic, mid SAPS, for use in petrol/gasoline & diesel engines including hybrid applications.

Application

A performance engine oil featuring NANODRIVE low friction technology for vehicles requiring a 0w30 viscosity, Designed for BMW/MINI, Mercedes-Benz and Volkswagen Audi Group (VAG) including Cupra, Lamborghini, Porsche Seat and Skoda.

Other coverage includes European and Asian manufacturers.

Recommended for

ACEA C3
API SN
BMW/MINI Longlife-04 (LL-04)
MB 229.52, MB 229.51, MB 229.31
Porsche C30
VW 504 00 / 507 00, VW 506 00 / 506 01,
VW 503 00 / 503 01, VW 502 00 / 505 01
Volkswagen Audi Group including Cupra,
Lamborghini, Seat and Skoda
Asian manufacturers

Typical Characteristics

Density @ 15°C, g/ml	0.844
Kinematic Viscosity @ 100°C, cSt.	11.64
Flashpoint, °C	>200

Features & Benefits

- Increased engine power and torque from award winning NANODRIVE low friction technology and synthetic ester formulation.
- Extended component life and reduced operating temperatures as a result of the instant lubrication provided by NANODRIVE low friction technology.
- “Track day ready”, high performance oil; delivers maximum engine performance whilst meeting manufacturer’s specifications and recommended oil drain interval for on-road use.
- Maximised efficiency and MPG delivered from the combined low viscosity and low friction NANODRIVE formulation.
- Covers a wide range of Asian/Japanese manufacturers including the latest petrol/gasoline & diesel engine technology including hybrid applications.

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website
www.millersoils.co.uk