



PRODUCT DATA SHEET



PRODUCT NAME/VISCOSITIES: **CLASSIC MINERAL 2T**

Product No	7933
Issue No.	2
Issue Date	26/02/19

DESCRIPTION:

A 2 stroke SAE 40 mineral engine oil. Solvent refined mineral base oils with high treatment of low ash additive formulated into an SAE 40 product.

APPLICATION:

By mixing with petrol in the ratio recommended by the equipment manufacturer – 50:1 maximum. SAE 40 ideal for vintage and classic 2 stroke engines. Suitable for outboard engines not requiring ashless oils.

USER BENEFITS:

- Low ash formulation.
- Reduced throttle sticking.
- Dyed 'blue' for easy recognition of the product and treated fuel.

PERFORMANCE PROFILE:

API/CEC, TC

TYPICAL CHARACTERISTICS:

SAE viscosity grade	40
Specific gravity at 15°C	0.892
Kinematic viscosity at 100°C	13.8cSt
Kinematic viscosity at 40°C	141cSt
Viscosity index	93
Pour point °C	-18
Flashpoint °C	230
Colour	Blue

HEALTH AND SAFETY:

Health and Safety Data Sheet 7933 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils technical department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk