PRODUCT NAME/VISCOSITIES:

CLASSIC SHOCK OIL 32

Product No	7922
Issue No.	2
Issue Date	26/02/19

DESCRIPTION:

A medium SAE 10 shock oil designed to provide sport handling characteristics.

APPLICATION:

Use as received for either top-up or full fluid replacement in shock absorbers or motorcycle forks.

USER BENEFITS:

- Shock Oil 32 is the 'medium' grade and will provide more 'sport' handling characteristics.
- Anti-wear and oxidation control.
- Corrosion protection and low foam characteristics.
- Thermal stability for long life.

PERFORMANCE PROFILE:

ISO 32/SAE 10

TYPICAL CHARACTERISTICS:

Specific gravity at 15°C	0.873
Kinematic viscosity at 100°C	6.4cSt
Kinematic viscosity at 40°C	30.2cSt
Viscosity index	172
Pour point °C	-30
Flashpoint °C	200

HEALTH AND SAFETY:

Health and Safety Data Sheet 7922 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils technical department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk