



PRODUCT DATA SHEET



PRODUCT NAME/VISCOSITIES: CLASSIC SHOCK OIL 46

Product No	7923
Issue No.	2
Issue Date	26/02/19

DESCRIPTION:

A heavy SAE 15 shock oil designed to provide competition handling characteristics.

APPLICATION:

Use as received for either top-up or full fluid replacement in shock absorbers or motorcycle forks.

USER BENEFITS:

- Shock Oil 46 is the heaviest grade and would normally be used for competition handling characteristics.
- Anti-wear and oxidation control.
- Corrosion protection and low foam characteristics.
- Thermal stability for longer life.

PERFORMANCE PROFILE:

ISO 46/SAE 15

TYPICAL CHARACTERISTICS:

Specific gravity at 15°C	0.878
Kinematic viscosity at 100°C	8.8cSt
Kinematic viscosity at 40°C	46cSt
Viscosity index	162
Pour point °C	-28
Flashpoint °C	218

HEALTH AND SAFETY:

Health and Safety Data Sheet 7923 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils technical department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk