

# TECHNICAL DATA SHEET



**Product code:** see below table    **Sector:** Industrial    **Issue No:** 3    **Issue Date:** 11/08/23

## MILLWAY RANGE

The Millway range is a blend of selected base stocks, anti-wear technology, with the inclusion of a tacky adhesive additive. Making it suitable for both horizontal or vertical slides and ways

### Application

Use as received for the lubrication of slide ways where smooth, stick-slip-free performance is required or where a tacky adhesive lubricant is required.

### Features & Benefits

- High lubricity prevents stick-slip of slide ways.
- Outstanding anti wear and anti corrosion properties.
- Non drip formula highly suitable for the lubrication of vertical surfaces.
- Careful selection of viscosity means hydraulic performance can be achieved.

### Typical Characteristics

|                                 |       |       |       |       |       |       |
|---------------------------------|-------|-------|-------|-------|-------|-------|
| Millway                         | 32    | 46    | 68    | 100   | 150   | 220   |
| Density @ 15°C, g/ml            | 0.860 | 0.865 | 0.877 | 0.885 | 0.899 | 0.903 |
| Kinematic Viscosity @ 40°C, cSt | 32    | 46    | 68    | 100   | 150   | 220   |
| Pour Point, °C                  | -15   | -15   | -15   | -15   | -15   | -6    |
| Flash Point, °C                 | 195   | 200   | 210   | 220   | 220   | 230   |
| Health & Safety/Product Code    | 5180  | 5310  | 5183  | 5210  | 5186  | 5301  |

### Technical & Health and Safety

T: 01484 475060

E: [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)

For H&S info or SDS, please visit our website [www.millersoils.co.uk](http://www.millersoils.co.uk)



**MADE IN BRITAIN**

**Millers Oils Ltd**

Brighouse West Yorkshire HD6 3DP UK

Tel: +44(0) 1484 713201

[www.millersoils.co.uk](http://www.millersoils.co.uk)