

The vessel is fitted with 35T A-Frame and working class ROV as well as extensive survey equipment capable of geophysical and geotechnical operations.

Contact Cyan Renewables

Australia

Perth Office

Level 10 12-14 The Esplanade Perth WA 6000

Ph: +61 8 9431 7431

South East Asia

Singapore Office

9 Raffles Place, #15-02 Republic Plaza Singapore 048619

Ph: +65 6265 1010

United Kingdom

Aberdeen Office

30 Abercrombie Court Prospect Road, Arnhall Business Park Westhill Aberdeenshire United Kingdom AB32 6FE

Ph: +44 1224 659950

MMA Crystal 克里司朵

Anchor Handling Tug Supply and Survey



General		Dimensions	
Official No	016607	LOA	70.05 m
Call Sign	ВНЈ Ј	Breadth - moulded	17 m
IMO No	9594212	Depth - moulded	7.5 m
Year Built	2012	Draft	6.1 m
Port of Registry	Tai Chung (台中)	GRT	2,763 T
Flag	Taiwan	NRT	829 T
Class	Republic of China	Deadweight	2,515 T
Class (Secondary)	American Bureau of Shipping	Free Deck Area (A-Frame fitted)	275 m ²
Notation	¥A1, Offshore Support Vessel (AH), Fire Fighting Vessel Class 1, Towing Vessel, &AMS,	Free Deck Area (A-Frame removed)	450 m ²
		Deck Strength	7.5 T/m ²
		Mezzanine Deck	84 m² @ 2T m² / W 12m x L 7m

cyanrenewables.com



MMA Crystal 克里司朵

Anchor Handling Tug Supply and Survey



2 x 5 m³/day

Performance		
0110	DUD	7.005
ВНР	BHP	7,965
Speed - Maximum	Knots	14
Speed - Economical	Knots	10
Bollard Pull	T	102.14

Tank Capacity		
Fuel Oil	m³	698.7
Fresh Water	m³	514.1
Potable Water	m³	514.1 (same to FW)
Foam	m³	15.7
Ballast Water	m³	1,336.4
Liquid Mud	m³	382
Cement	m³	200
Dispersant	m³	15.7
Dry Bulk	m³	(Refer to Cement)
Methanol	m³	NÁ

DIY DUIK	1111	(Refer to Cement)
Methanol	m³	NA
D: 1 D :		
Discharge Rates		
Fuel Oil		1 x 117 m ³ /hr @ 80 m head
Fresh Water		1 x 120 m ³ /hr @ 90 m head
Ballast / Drill Water		1 x 120 m ³ /hr @ 90 m head
Potable Water		1 x 120 m ³ /hr @ 90 m head
Dry Bulk		2 x 20 m ³ /hr @ 5 bar
Liquid Mud / Brine		2 x 75 m ³ /hr @ 95 m head

Machinery / Propulsion	
Main Engines Bow Thruster Stern Thruster Shaft Generators	2 x MAK 9M25, 2,970 kW 2 x 600 kW tunnel type 1 x 600 kW tunnel type 2 x 1,800 kW
Generators	2 x Volvo Penta D12 MG, 370 kW
Emergency Generators Propulsion Power Supply Details	1 x 99 ekW @ 1,800 rpm 2 x CPP 440 V / 60 Hz
Deck Equipment	
Crane	PALFINGER Hyd Deck Crane PTM 400 (2 T @ 12m / 5.9 T @ 2.2m)
Capstan	2 x Electrohydraulic Brattvaag
Towing Winch	1 x Rolls Royce Electro Hydraulic Waterfall
Capacity	200 T @ 0-10 m/min
Wire Capacity	58 mm x 1400 m
Brake Holding	250 T
Anchor Handling Winch	1 x Rolls Royce Electro Hydraulic Waterfall
Capacity	200
Wire Capacity	76 mm x 800 m
Brake Holding	250 T
Shark Jaw	1 x 300 tonne Karmfork
Towing Pin	2 x 300 tonne Karmoy
Tugger Winch	2 x 12 tonne Hydraulic
Wire Capacity	24mm x 220 m
Brake Holding	15 T
Stern Roller	2.2 m x 4.8 m (250 tonne capacity)
Deck Voltage & Sockets - Quantity & Voltage	2 x 440V, 2 x 220V

SWL	35 T
Height (underside cross member)	11.7 m
Reach outboard	4 m
Rescue Boat & Fire Fighting	
Rescue Boat	1 x 6 person
FiFi Class	Neuvisa RR-40 RB Class 1
Dynamic Positioning	
	MT Class II DYNPOS
DP - System	/ DP2
DGPS - Quantity	2 x Fugro
Fanbeam - Quantity	1 x Cyscan
HiPAP	Sonardyne Ranger2 (HPT5000)
Accommodation	
	Qty
Cabin (2 Berth)	18
Cabin (Single Berth)	10
Total Accommodation	46 Pax
Communication Equipment	Otro
Navtex Receiver	Qty 1
AIS	1
Watch Alarm	1
SSB	1
Intercom	1
Inmarsat-C	2
EPIRB	1
GMDSS VHF Radio (MF/HF)	2 x VHF, 1 x MF/HF
GMDSS Handheld VHF	3

Subsea / ROV Equipment	
Bridge Survey Room Forecastle Deck Survey Rooms	1 (online navigation) 2 (1 x client, 1 x survey)
ROV	Swift10 Work Class ROV system
Survey Communications	Quinsey Śurvey Navigation System 2 x Veripos LD8 DGNSS Sonardyne Ranger 2 USBL for subsea acoustic tracking Teledyne Meridian Surveyor Gyro Compass Over the side pole for multi-sensor options Intellian V130NX VSAT Robustal R2000-EL42 4G Modem Clear Comms
Navigation Equipment	
Magnetic Compass Gyro Compass c/w Autopilot GPS Navigator Radar Speed Log	Qty 1 3 1 2 1
Other Equipment	

Water Maker